ALEPH VERSION 17.01/18.01

ALEPH Tables

© Ex Libris Ltd., 2006
Last Update: March 6, 2006
Document Version 1.0
Code: A-ver18-ALTab-1.0

CONFIDENTIAL INFORMATION

The information herein is the property of Ex Libris Ltd. or its affiliates and any misuse or abuse will result in economic loss. DO NOT COPY UNLESS YOU HAVE BEEN GIVEN SPECIFIC WRITTEN AUTHORIZATION FROM EX LIBRIS LTD.

This document is provided for limited and restricted purposes in accordance with a binding contract with Ex Libris Ltd. or an affiliate. The information herein includes trade secrets and is confidential.

DISCLAIMER

The information in this document will be subject to periodic change and updating. Please confirm that you have the most current documentation. There are no warranties of any kind, express or implied, provided in this documentation, other than those expressly agreed upon in the applicable Ex Libris contract.

Any references in this document to non-Ex Libris Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Ex Libris product and Ex Libris has no liability for materials on those Web sites.

Copyright Ex Libris Limited, 2006. All rights reserved.
Documentation produced March 2006.
Document version 1.0.
Web address: http://www.exlibrisgroup.com

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
5426_to_unicode2	Translates ISO 5426 to Unicode	Server	alephe/unicode			
853_chrono	Chronographic terms used by the 853 field for Serials holdings	Serials	alephe/tab			
853_numbering	Numbering terms used by the 853 field for Serials holdings	Serials	alephe/tab			
aleph_start	Version and/or platform-dependent settings	Server	alephe/root	Various new and updated parameters. Check the Release Notes for more detail	X	X
aleph_start_private	Client-specific settings of aleph_start_505	Server	alephe/root			
aleph_startup	Startup definitions	Server	alephe/root			
allowed_languages	Language codes	Server	alephe/tab			
bib_format	Paragraph styles for bibliographic display in forms	Printing	XXX50/tab	Formats of GUI forms (such as user-cash, userloan, item-expand and others) have been set to use edit_paragraph code 303.	X	
cash_09_translate	Translate sublibrary to a department code, for the cash_09 report purposes	Circulation	XXX50/tab			
check_circ	Error messages linked to circ tables	Circulation	aleph/error_<lng>	The directory error_<lng> has moved from alephe/error_<lng> to aleph/error_<lng>	X	
check_circ_override	Minimum password level for each check_circ procedure	Circulation	XXX50/tab			
check_doc	List of check_doc programs for Cataloging	Cataloging	XXX01/tab			
check_doc (error messages)	System driven validation messages for check_doc programs	Cataloging	aleph/error_<lng>	The directory error_<lng> has moved from alephe/error_<lng> to aleph/error_<lng>	X	

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
check_doc.<lng>	Table driven validation messages for check_doc programs	Cataloging	tab			
check_doc_doc	Checks of field occurrence, and of dependency between fields, in Cataloging	Cataloging	tab	header updated; header incorrectly stated that "99" indicates unlimited number of occurrences.	X	
check_doc_field_006	Checks for tag 006 (MARC 21)	Cataloging	XXX01/tab			
check_doc_field_007	Checks for tag 007 (MARC 21)	Cataloging	XXX01/tab			
check_doc_field_008	Checks for tag 008 (MARC 21)	Cataloging	tab			
check_doc_field_ldr	Checks for the LDR tag (MARC 21)	Cataloging	tab			
check_doc_line	Checks of logical structure/connections within a single occurrence of a field	Cataloging	tab			
check_doc_line_contents	Checks contents within a single occurrence of a field	Cataloging	tab			
check_doc_mandatory	Checks of forbidden (or acceptable-with-a-trigger type) errors	Cataloging	tab			
check_doc_new_acc	Fields that should be ignored while checking for unique Headings (ACC) index entries	Cataloging	tab			
check_doc_new_acc_aut	Fields that should be ignored while checking for unique Headings (ACC) index and Authorities entries	Cataloging	XXX01/tab			
check_doc_tag_text	Checks of pre-defined texts for sub-fields (from pc_tab/catalog/tag_text)	Cataloging	tab			
check_doc_unique_index	Fields that should be ignored while checking for unique Direct (IND) index entries	Cataloging	tab			
circ_logger	Error messages linked to the circulation log	Circulation	aleph/error_<lng>	New	X	

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
codes.<lng>	Editable field codes and aliases	Cataloging	pc_tab/catalog			
drm_routines	Check routines for user authorization and payment related to digital rights	OPAC	XXX01/tab			
edi_in_attr	EDI incoming messages attributes	Acquisitions/Serials	XXX50/tab			
edi_out_attr	EDI outgoing messages attributes	Acquisitions/Serials	XXX50/tab	Header updated 7 EDI-OUT-BUDGET Y (default) = Budget code will be sent in relevant EDI outgoing messages. N = Budget code will not be sent in EDI messages.	X	X
edit_doc.<lng>	Document format definition for Web/GUI and printouts	Web/GUI/Printing	tab			
edit_doc_777	Record conversion format for export to reference manager such as Endnote	Printing	tab			
edit_doc_999.<lng>	GUI/Web OPAC display of the Full format of a record plus links	Web/GUI	tab			
edit_doc_999_aut_aut_lib.<lng>	Display of AUT information on cross references	OPAC	XXX01/tab			
edit_field.<lng>	Formatting of individual fields for the display of bibliographic information	Web/GUI/Printing	tab			
edit_paragraph.<lng>	Paragraphs in bibliographic information displays	Web/GUI/Printing	tab	Added paragraph identifier 300. This is the default in bib_format.	X	
expand_doc_bib_z30	Defines which fields from the item record (Z30) are expanded into the bibliographic record	Indexing	tab			
expand_doc_bib_z403	Defines which fields from the object data record (Z30) are expanded into the bibliographic record	Cataloging	tab	New		X
fix_doc.<lng>	fix_doc routines included in the Catalog/ Menu/Edit/Fix record	Cataloging	pc_tab/catalog			

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	drop-down menu					
form_description.<lng>	Determines the subject line for e-mail printouts	Printing	tab			
form_print_method	Print method for printouts	Printing	tab			
form_sub_library_address	Address type for Acquisitions, ILL & Circulation forms	Printing	XXX50/tab	Header updated	X	
formats.<lng>	List of formats for Cataloging	Cataloging	pc_tab/catalog			
generic_fix	Sample table of a processing script for fix_doc_do_file_08 and p_file_08	Cataloging	XXX01/tab/import			
job_list	Scheduling of regular programs that run on the job daemon	Batch Processes	alephe/tab			
job_list.conf	Definition of daily and weekly schedules for the job_list	Batch Processes	alephe/tab			
ldap.conf	LDAP configuration file	Circulation	USR00/tab			
library_relation	Relation between libraries by library type	System	alephe/tab	Header updated	X	
license	Parameters pertaining to the institution's **ALEPH 500** license are defined here, as per the parameters issued by ***Ex Libris.***	Server	alephe/tab			
marc_country_codes	Country codes used in MARC fixed fields	Cataloging	alephe/tab			
marc_exp.dat	Sub-fields to be included in the open form in cataloging	Cataloging	pc_tab/catalog			
marc_language_codes	Language codes used in MARC fixed fields	Cataloging	alephe/tab			
marc8_xxx_to_unicode	Character conversion tables	Unicode	alephe/unicode			
no_utf_mac	Defines a list of MAC browsers/versions (user agents) that do not fully support UTF-8.	Web	alephe/tab			
no_utf_pc	Defines a list of browsers/versions (user agents) that do not fully support UTF-8.	Web	alephe/tab			
oclc_server_defaults	Used for defining environment variables for the OCLC server	Server	alephe/root			
path_convert	Re-direction of directories for	Server	tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	sharing between libraries					
pc_server_defaults	Defaults for the pc server	Server	alephe/root			
pc_tab_acq_fast_cat.<lng>	Fields for fast cataloging in the Acquisitions module	Acquisitions	XXX01/tab XXX50/tab			
pc_tab_cat_conv	Conversion program + parameters for converting imported records in the Cataloging Client	Cataloging	XXX01/tab XXX10/tab	Table added to XXX10/tab environment		
pc_tab_circ_fast_cat.<lng>	Fields for fast cataloging in the Circulation module	Circulation	XXX01/tab XXX50/tab			
pc_tab_col.<lng>	Definition of columns in GUI screens	GUI - General	XXX01/tab	New definitions	X	X
pc_tab_exp_field.<lng>	Field values for the GUI pull down menus	GUI - General	XXX50/tab	Fields added: BINDING-PRIORITY BINDING-TYPE The menu BINDDISCARD- TYPE has replaced the menu DISCARD-TYPE Added a description of the ILL outgoing request status 'EXP' to ILL-EXT-REQSTATUS	X	
pc_tab_exp_field_extended.<lng>	Sub-library sensitive field values for the GUI pull down menus	GUI - General	XXX50/tab			
pc_tab_fast_circ	Parameters for fast circulation	Circulation	XXX50/tab			
pc_tab_find.<lng>	Fields for searching for a record in the ILL module	ILL	XXX50/tab			
pc_tab_scan.<lng>	Fields for searching for a record in the ILL module	ILL	XXX50/tab			
pc_tab_sear.<lng>	Definition of GUI SEARCH search options	GUI - Search	XXX01/tab XXX10/tab			
pc_tab_short.<lng>	Display of the 'Brief format' of a record in the Search function	GUI - Search	tab	Header updated	X	
pc_tree_c1501	Messages related to the	GUI - General	aleph/error_<lng>			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	Navigation Windows in the online **ALEPH** modules					
permission.dat	Allowed and denied tags for different users	Cataloging	pc_tab/catalog			
prof_alephe	Used to set the ALEPH environment needed for running scripts	System	alephe/root			
remote_catalog.dat	List of remote catalogs for Z39.50 Update Service	Cataloging	pc_tab/catalog			
rep_tab_short.<lng>	Fields for printing bibliographic information in column form for report p-print-08	Printing	tab			
scancode.dat	Headings indexes to be searched (on the field or sub-field level) during cataloging	Cataloging	pc_tab/catalog	Table is now base sensitive. The structure of the table has changed		
server_ip_allowed	Access definitions to Web and PC servers	Server	alephe/tab			
tab_85x_import	Matching fields for p-serial-52 (import 85XX records)	Serials	XXX50/tab			
tab_96_def	Default values for p-file-96 (Generic Vendor Records Loader)	Cataloging	XXX01/tab/import	New	X	
tab_98_def	Default values for p-file-98 (BNA loader)	Cataloging	XXX01/tab/import			
tab_99_def	Default values for records/items created by p-file-99 (Marcive loader)	Cataloging	XXX01/tab/import			
tab_abbrev	Expanding abbreviations to full text	Cataloging/OPAC	XXX01/tab			
tab_acq_index	Display of bibliographic fields in the order index	Acquisitions	XXX50/tab			
tab_alephadm.<lng>	Table name definition for the ALEPHADM module (for BIB library tables)	ALEPHADM	tab alephe/tab			
tab_attr_sub_library	IP-based sublibrary relationships with regard to loan/return, cash and reading room management	Circulation	XXX50/tab	Moved from alephe/tab to the tab directory of the ADM library		
tab_aut	List of AUT libraries for use in	Cataloging	XXX01/tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	matching BIB library headings					
tab_base.<lng>	Definition of databases	OPAC/Search	alephe/tab			
tab_base_count	Logical bases (record counters) in Web and GUI browse list	OPAC/Search	alephe/tab			
tab_binding	Definition of binding procedures	Serials	XXX50/tab			
tab_block_circ	Parameters for blocking loans	Circulation	USR00/tab			
tab_booking	Defining head/tail times to the starting/ending of booking request	Circulation	XXX50/tab	New	X	
tab_bor_address	Chronological periods for patron address types	Circulation	USR00/tab			
tab_bor_id.<lng>	Mangement of system-wide user IDs	Circulation	USR00/tab	Correction to header	X	
tab_buf_z403	List of programs to build buf_z403 (used to govern access to electronic resources.)	OPAC	XXX01/tab			
tab_cat_hidden_fields	Block specific fields from being displayed in Cataloging	Cataloging	XXX01/tab			
tab_ccl_boolean_operators	Language definitions of CCL Boolean operators	OPAC/Search	alephe/tab			
tab_character_conversion_line	Unicode conversion tables	General	alephe/unicode			
tab_check_circ	Checks for loan/return/renew in Circulation	Circulation	XXX50/tab	New lines for ILL-L and ILL-C checks. Check 2_e explanation corrected. The following section description was added: RENEW-W-G	X	
tab_checksum	List of checksum programs	GUI	XXX50/tab			
tab_circ_log.<lng>	Logging of circulation transactions	Circulation	XXX50/tab	New	X	
tab_code_prefix	Prefixes for budget code, vendor code and ILL supplier code	Acquisitions/ILL	XXX50/tab			
tab_days	Definition of days and their codes (used for short loans)	OPAC/Circulation	alephe/tab			
tab_dbs.<lng>	Configuration for Advanced Library Statistics	General	XXX50/tab			
tab_delinq.<lng>	Delinquency codes and blocking	Circulation	XXX50/tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	of permissions in Circulation					
tab_delivery_locations.<lng>	Delivery locations for booking requests	Circulation	XXX50/tab			
tab_events.<lng>	List of event types for statistics (Z35and Z69)	OPAC/Circulation	XXX01/tab XXX50/tab	Header changed to reflect New Z69 table for recording events in the OPAC. **Version 16!!!**	X	
tab_exp_own.<lng>	Defines the possible values for the OWN field	Passwords	XXX50/tab			
tab_expand	List of expand programs merging linked records (from the same and different libraries) for display and indexing	OPAC/Cataloging	tab			
tab_expand_duplicate_field	Definitions for expand_doc_duplicate_field, which duplicates a field	OPAC/Cataloging	tab			
tab_expand_external	Definitions for expand_doc_external, that splits external fields	OPAC/Cataloging	tab			
tab_expand_extract	Creation of a new virtual field for indexing from an existing MARC sub-field	Indexing	tab			
tab_expand_join	Creation of a new virtual field for indexing by joining two or more MARC fields	Indexing	tab			
tab_expand_join_simple	Creation of a new virtual field for indexing by joining all occurrences of two MARC fields	Indexing	tab			
tab_expand_local_notes.conf		OPAC	XXX01/tab			
tab_expand_sort	Sub-fields arranged in non-alphabetical order for sorting by the expand_doc_sort routine	OPAC/Search	tab			
tab_expand_split	Sub-fields to be indexed or displayed in a different (non-alphabetical) order	OPAC/Search	tab			
tab_export	Retrieval definitions for selection of records to be	Cataloging	alephe/tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	exported by p-export-01					
tab_export_03	Configuration for smart barcode export routine	Cataloging	XXX50/tab			
tab_fast_patron_register	Default values for fast patron registration	Circulation	USR00/tab			
tab_filing	Definition of filing and normalization routines	OPAC/Search	tab	Explanation re filing for issn/isbn updated for clarity		
tab_filing_call_no	Definition of filing routines for items (based on the LC call nos.)	Cataloging	XXX50/tab			
tab_fix	List of fix_doc programs in Cataloging	Cataloging	tab	New lines added to default setup of the XXX10 library	X	X
tab_fix_local_notes.conf	Defines the order of HOL records to be expanded into the BIB record	Cataloging	XXX01/tab			
tab_fix_z103	Item and HOL filtering	Cataloging	XXX01/tab	fix_z103_filter_base can use expand-routines		
tab_fix_z103_local_notes.conf	Used for filtering HOLDINGS and ITEMS information in the Web OPAC	Cataloging	XXX01/tab			
tab_hld_stmt	Holdings summary statement building	OPAC	XXX50/tab			
tab_hol_item_create	Defines where in the bibliographic record item and holdings data elements are to be found for the creation of items and holdings by p-manage-50	Cataloging	XXX01/tab/import			
tab_hol_item_map	Mapping bibliographic values into the relevant holdings and/or items values	Cataloging	XXX01/tab/import			
tab_hol_mapping	Definition of mapping values when creating records with p-manage-500	Cataloging	XXX01/tab	Header changed Updated. Col. 3 can have many arguments	X	
tab_hold_request	Checks for hold requests	Circulation	XXX50/tab	Adding new section BKCIRC used in the	X	X

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
				Circulation client when creating/updating a request. New programs added which are relevant only for booking requests: Description re XML-CIRC added to the header. Heading updated for booking request checks		
tab_hold_request_form	Defining hold request forms for use in the OPAC	Circulation	XXX50/tab			
tab_ill_charge	Parameters for charging for ILL requests	ILL	XXX50/tab			
tab_ill_in_index	Display of bibliographic fields in the ILL incoming requests' index	ILL	XXX50/tab			
tab_ill_index	Display of bibliographic fields in the ILL outgoing requests' index	ILL	XXX50/tab			
tab_io_remote	IP addresses for server to server connections	Server	alephe/tab			
tab_item_history.<lng>	Display of fields in the Item history screen	Cataloging	alephe/tab			
tab_item_list_order	Items display order in the OPAC and Search according to sublibraries of each base	OPAC/Search	XXX50/tab			
tab_itm_mapping	Definition of mapping values when creating records with p-manage-500	Cataloging	XXX01/tab			
tab_label.<lng>	Prefixes for spine label printouts	Cataloging	XXX01/tab			
tab_label_parse	Splitting call number and item description when generating item labels	Cataloging	XXX50/tab			
tab_late_return	Defines time and rate for fine method "F" (tab16)	Circulation	XXX50/tab			
tab_library_group	Grouping of libraries to share	System	XXX50/tab	The functionality has	X	

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	the same batch processes.			changed. If your library is managed by another library using an $alephe_tab /tab_library_group definition, the utilities will not allow you to start or stop jobs.		
tab_locate	Procedures for locating a record in other libraries in OPAC, Cataloging, Search, ILL	OPAC/GUI	alephe/tab			
tab_location_name.<lng>	Location names for Z39.50 server	Z39.50	XXX01/tab XXX10/tab	New	X	
tab_map_privileges	Defining the types of global ALEPH Z305 record	Circulation	XXX50/tab	New		X
tab_mapping	Mapping values when creating records with the RLIN Loader (UTIL E/3)	Cataloging	alephe/tab	Better basic setup	X	
tab_mapping_mng500	Definition of mapping values when creating records with p-manage-500	Cataloging	XXX01/tab XXX50/tab			
tab_match	Match specifications for importing files	Cataloging	XXX01/tab			
tab_match_acc	Fields to check against the headings (ACC) index	Cataloging	tab			
tab_match_script	Match specifications for checking input file against the database	Cataloging	tab			
tab_merge	List of merge routines	Cataloging	XXX01/tab			
tab_merge_adv_overlay	Advanced routines for the merging of document records	Cataloging	tab			
tab_merge_overlay	Fields to retain when overlaying (merging) catalog records	Cataloging	tab			
tab_mime_type	Extension definitions for use in save-function in the OPAC	OPAC	alephe/tab			
tab_month	Month codes and abbreviations in different languages	General	alephe/tab			
tab_move_record	List of programs for moving	Cataloging	XXX01/tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	records					
tab_oclc	OCLC server configuration table	Cataloging	XXX01/tab	Small change to header – col. 5. The header was changed to further support OWN.	X	
tab_own	Cataloging OWN permissions and filter	Cataloging	tab	Header updated.	X	
tab_photo_request	Checks for photocopy requests	Circulation	XXX50/tab			
tab_pinyin	Definition of fields for fix_doc_add_pinyin_check_sub9 and fix_doc_add_pinyin_insert_sub9	Cataloging	XXX01/tab			
tab_preferred	Defines settings for preferred records when merging document records	Cataloging	XXX01/tab			
tab_rlin	Settings for importing RLIN records	Cataloging	XXX01/tab			
tab_roster	Controls the order that the roster batch job (p-cir-79) moves requests from institute to institute	Circulation	XXX50/tab	New		
tab_service	Table for defining services in the Web OPAC	OPAC	XXX01/tab XXX10/tab			
tab_sfx	Defines under which conditions the SFX button will appear in the Web OPAC.	OPAC	XXX01/tab			
tab_sfx_denied	Defines under which conditions the SFX button will not appear in the Web OPAC.	OPAC	XXX01/tab	New	X	
tab_sip2.conf	Self-check definitions for SIP2	Circulation	XXX50/tab			
tab_sip2_alert	Self-check field alert definitions	Circulation	XXX50/tab			
tab_sip2_translate	Self-check field definitions	Circulation	XXX50/tab			
tab_sort	Fields for sorting in OPAC and GUI Search	OPAC/Search	tab			
tab_sub_lib_sort	Definition of sublibraries' list sorting in various ALEPH functions	General	XXX01/tab	Web Customize Brief View screen - For LOC and PST lines WWW-FULL-LOC-PST		

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
tab_sub_library.<lng>	List of libraries and sublibraries	General	alephe/tab	Header updated. Tab27 added to the explanation of library types 3 and 4	X	
tab_sub_library_address.<lng>	Addresses of sublibraries for printouts	General	alephe/tab OR XXX50/tab	Header updated	X	
tab_subfield_punctuation	Standard punctuation to be added to sub-fields for OPAC display	OPAC	XXX01/tab XXX10/tab			
tab_suf_bor_defaults	Shared patron statuses	Circulation	alephe/tab			
tab_suf_default	Shared user definitions	Circulation	alephe/tab			
tab_suf_lib	Shared user definitions	Circulation	alephe/tab			
tab_tag_text	Default tag values when creating new records	Cataloging	tab			
tab_type_config.<lng>	Specifications of new fields created by expand_doc_type routines	Indexing	XXX01/tab			
tab_vat_percent.<lng>	Codes for VAT percentages (for ACQ invoices)	Acquisitions	XXX50/tab			
tab_vendor_sub_lib	Sublibrary specific and generic vendor fields	Acquisitions	XXX50/tab			
tab_version	Client definitions to access the pc_server	Server	alephe/tab			
tab_weights	Weight factors for determining candidate records	Cataloging	XXX01/tab			
tab_word_breaking	Definition of word breaking procedures	Indexing	XXX01/tab XXX10/tab			
tab_xyz	Defines the "XYZ" index that should be used to strip subject subdivisions.	Indexing	XXX01/tab			
tab_yankee_def	Default values the YBP loader (p-file-96)	Acquisitions	XXX01/tab/import			
tab_z0101	Brief record (Z0101) structure based on format, index and field of origin	Indexing	XXX01/tab			
tab_z0101_text	Text codes and definitions for the brief record	Indexing	XXX01/tab			
tab_z103	Programs for building links	Server	tab			

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	between records					
tab_z105	Record update messages to be sent to other libraries	General	tab	Header updated to describe the usm50 to usm01 messages that are relevant for SDI. New message type for Union Catalog	X	
tab_z105_filter	Fields to retain when replicating z105 messages (ue_11)	General	tab			
tab_z105_z30	Defines when a message from one library to another will not be created following a Z30 update	General	XXX50/tab	New	X	
tab_z121	Definitions for the web service search engine	OPAC	XXX01/tab			
tab_z30	Default values for items created using the OCLC server and RLIN loader	Cataloging	XXX50/tab	Header changed. Marcive is now uses this table too. Columns 9-11 were added to further support OWN. Better basic setup Col. 1: The code DEF can used as a default holding code. This is possible ONLY for a single ADM environment. Multi-adms must define all possible holding codes in their tab_z30 tables.	X	X
tab_z30_sort	Sort options for items	OPAC/GUI	XXX01/tab XXX50/tab	Header updated	X	
tab_z31_sort	Definition of cash (z31) sort types in various ALEPH functions	Circulation	XXX50/tab			
tab_z311	Counters for z30-call-no/z30-call-no-2 and z30-inventory-number	Cataloging	XXX50/tab			
tab_z403_directory.<lng>	Maps directories of OBJECT	ADAM	alephe/tab	New	X	

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	files between libraries					
tab_z403_extension.<lng>	Maps extensions to mimetypes and icons for the Web OPAC	ADAM	alephe/tab	New	X	
tab_z403_info.<lng>	Defines which fields from the object record (Z403) are expanded into the object info.	ADAM	alephe/tab	New	X	
tab_z36_sort	Definition of loan (z36) sort types	Circulation	XXX50/tab	New	X	
tab00.<lng>	Codes and names for indexes: Words, Headings (ACC) and Direct (IND) indexes	Indexing	tab	Help on col. 2 was changed	X	
tab01.<lng>	Codes and names of cataloging fields	Indexing	tab			
tab02	Initial non-filing words/articles for the Headings index	Indexing	tab			
tab04	Conversion of fields between formats	Cataloging	tab			
tab05.<lng>	Captions for links between records	OPAC/Search	XXX01/tab			
tab06	Search words not to be highlighted in the full view of a record on the Web OPAC (e.g., “the”)	OPAC	XXX01/tab			
tab07	Defines the links between Authority Headings	Cataloging	XXX01/tab			
tab11_acc	Assignment of cataloging records’ fields to Headings indexes	Indexing	tab			
tab11_aut	ACC fields used to create hypertext links to FIND and BROWSE from the AUT record	Indexing	XXX01/tab			
tab11_ind	Assignment of fields to Direct indexes	Indexing	tab			
tab11_word	Assignment of fields to Word indexes	Indexing	tab			
tab12	Translation of ALEPH codes to Dublin Core XML elements	Z39.50	XXX01/tab	New		
tab14	Item re-shelving time	Circulation	XXX50/tab			

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
tab15.<lng>	Defines the item statuses and various parameters connected to these statuses.	Circulation	XXX50/tab	Header regarding col. 11 corrected. New col. 16 added for control of booking permissions	X	
tab16	Due dates, fines and limits on borrowing	Circulation	XXX50/tab	New cool 26. Max no. booking requests. New col. 27 - Adjust due date and hour		
tab17	Library open hours	Circulation	XXX50/tab			
tab18.<lng>	Cash transaction types	Circulation	XXX50/tab	Adding new cash types 0091-0094 for itembooking: Added heading explanations for transaction types 84 and 85	X	X
tab20	Links from BIB Headings to AUT Records	Cataloging	XXX01/tab			
tab22	Fields for short doc format (Z13)	General	XXX01/tab			
tab24	Delivery time slots from the Depository	Circulation	XXX50/tab	New column 3 description	X	
tab25.<lng>	Item material types	Cataloging	XXX50/tab			
tab27	Hold requests send method configuration	Circulation	XXX50/tab	Adding new column - request-type, in order to differentiate between sendmethods of Hold requests and Booking-Requests. New process options in col. 5 – types 6, 7, & 8	X	X
tab30	Patron registration renewal	Circulation	XXX50/tab			
tab31	Patron statuses defaults	Circulation	XXX50/tab	Two new columns: col. 20 - Item booking permission and col. 21 - Booking		

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
				ignore closing hours		
tab32	Overdue letter intervals	Circulation	XXX50/tab			
tab33.<lng>	Defines the format of the BIB-ADM record that displays in the navigation window in the various GUI modules	GUI	XXX01/tab XXX50/tab			
tab34	Lost materials costs	Circulation	XXX50/tab	Header updated.	X	
tab35	Location numbers and other information for EDI orders	Acquisitions	XXX50/tab			
tab36	Defaults for automatic opening of monograph items in Acquisitions	Acquisitions	XXX50/tab			
tab37	Pick up list configuration for hold requests	Circulation	XXX50/tab	tab37 header corrected to allow hashes in column 1	X	
tab37_booking_delivery	Booking Requests delivery configuration	Circulation	XXX50/tab			
tab37_booking_pickup	Booking Requests pick up list configuration	Circulation	XXX50/tab	New - defines valid delivery locations for booking requests tab37_booking_pickup Booking Requests pick up list configuration Circulation XXX50/tab New - defines valid pickup locations per Item/Patron statuses.	X	
tab37_campus_filter	Hold requests filter table	Circulation	XXX50/tab	Header of column 3 changed to COL 3. 2; TEXT, UPPER;	X	
tab37_campus_preferred	Preferred supplier list for hold requests	Circulation	XXX50/tab	Header corrected to allow hashes in column 1	X	
tab38	Photocopy request configuration	Circulation	XXX50/tab			
tab39	Hold request's daemon configuration	Circulation	XXX50/tab			
tab40.<lng>	Collection codes and names	General	XXX50/tab			

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
tab41	Photocopy request's daemon configuration	Circulation	XXX50/tab	Header corrected – col. 6	X	
tab42	Automatic update of the processing status field in the item record.	GUI	XXX50/tab			
tab43	Advanced booking of items	Circulation	XXX50/tab			
tab44	Definition of how long requested items will be kept on the hold shelf	Circulation	XXX50/tab			
tab45.<lng>	Order transaction types for order log	Acquisitions	XXX50/tab			
tab46.<lng>	ILL request log transaction types	ILL	XXX50/tab			
tab47.<lng>	ILL supplier material type and copyright agreement	ILL	XXX50/tab			
tab48.<lng>	General Invoice payment defaults	Acquisitions	XXX50/tab			
tab100	Switch settings for different aspects of the system	System	tab	Numerous new flags. Check Release Notes for more detail.	X	X
tag_text.dat	Pre-defined text options for sub-fields	Cataloging	pc_tab/catalog	Header change to col. 3	X	
tagonnew.dat	Default fields for a new record	Cataloging	pc_tab/catalog			
unicode_to_filing_01	Unicode character conversion equivalencies for sorting	General	alephe/unicode			
unicode_to_word_gen	List of Unicode character conversion equivalencies, to be used when creating records in the WORDS file	General	alephe/unicode			
union_global_param	Union catalog de-duplication parameters	Cataloging	alephe/tab			
union_preferred	Weighting table for determining which of two matching records is the preferred record	Cataloging	XXX01/tab			
user_function.<lng>	User authorization definitions and codes	Security	alephe/tab	Adding tree functions for item-booking. Some SERIAL lines have been removed.	X	
verde_variables	Values for connecting Verde via	Acquisitions/Serials	XXX50/tab	New	X	

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
	external services					
www_f_func	Functional codes linked to HTML action commands	OPAC	alephe/tab			
www_f_heading	Messages to the patron in the Web OPAC	OPAC	aleph/error_<lng>	The directory error_<lng> has moved from alephe/error_<lng> to aleph/error_<lng> line 9017 edited for clarity	X	
www_f_sort_heading.<lng>	Sort types for display in the Web OPAC	OPAC	XXX01/tab XXX10/tab			
www_f_tab_short_999	Custom brief display formats for Web OPAC	OPAC	XXX01/tab XXX10/tab			
www_r_heading	Messages to the patron in the Course Reading Module	OPAC	aleph/error_<lng>	The directory error_<lng> has moved from alephe/error_<lng> to aleph/error_<lng>	X	
www_server.conf	Defaults for the web server	Server	alephe	SFX settings moved to aleph_start setenv ill_borrower_status setenv www_dn_view_display	X	X
www_tab_myshelf_short.<lng>	Brief display format of records in My e-Shelf	OPAC	USR00/tab	New Changed, line added: 9 L Availability L ## AVAIL	X	X
www_tab_self_check	ip-based sub-library relationships for Web self check functionality	Circulation	alephe/tab	New		
www_tab_short.<lng>	Brief display of records in Web OPAC	OPAC	tab			
www_x_func	X Server function definitions	OPAC	alephe/tab			
Z39_gate.conf	Definition for Z39 gate	Z39.50	alephe/tab/z39_gate			
z39_gate_<library>.conf	Definition of external Z39.50 Databases	Z39.50	alephe/tab/z39_gate			
z39_gate_error_list	List of errors which might be returned by our Z39.50 gate	Z39.50	alephe/tab/z39_gate			

© Ex Libris Ltd., 2006

Table name	Description	Function	Location[1]	Changed or New	Ver 17	Ver 18
z39_server.conf	Profile of ALEPH Z39.50 server	Z39.50	alephe/tab/z39_server			
z39_server_<library>.conf	Translation of ALEPH codes to Z39.50 codes	Z39.50	alephe/tab/z39_server			
z39_server_elements	Defines fields and sub-fields for each base and element set name	Z39.50	alephe/tab/z39_server			
z39_server_update_errors	Mapping of Aleph check_doc errors to Z39.50 update errors	Z39.50	alephe/tab/z39_server			
z39_target_error_list	List of errors which might be returned by a Z39.50 target	Z39.50	alephe/tab/z39_gate			

[1] XXX01 refers to a BIB type of library
XXX50 refers to an ADM type of library
XXX60 refers to a HOL type of library
XXX10 refers to an AUT type of library
XXX20 refers to an ILL type of library
XXX30 refers to a Course Reading type of library
USR00 refers to a User (Patron) type of library
No reference to a specific library type, indicates that the related table can be defined (found) in more than one type of library

© Ex Libris Ltd., 2006