

Z309 – Circulation Logger

The Z309 table acts as a circulation "log" file. The Circulation Logger is a tool that enables a staff user to view and filter a patron's circulation activities. Loan and cash activities are displayed as part of a transaction, starting from the time that an item has been loaned until it has been returned and starting from the time that a cash charge has been created until it has been fully paid.

In the following table, (X) denotes an alphanumeric field and (9) denotes a numeric field. All alphanumeric fields are left-aligned with leading spaces, all numeric fields are right-aligned (with leading zeroes, where relevant). Decimal positions are indicated by the symbol V. The total number of decimal digits is designated by the number of nines following the V.

```
01
  Z309.
  02 Z309-REC-KEY.
    03 Z309-ID
                                  PICTURE X(12).
    03 Z309-SEQUENCE
                                  PICTURE 9(15).
  02 Z309-REC-KEY-2.
    03 Z309-LOAN-NUMBER
                                  PICTURE 9(9).
  02 Z309-REC-KEY-3.
    03 Z309-DOC-NUMBER
                                  PICTURE 9(9).
    03 Z309-ITEM-SEQUENCE
                                  PICTURE 9(6).
  02 Z309-REC-KEY-4.
    03 Z309-CASH-ID
                                  PICTURE X(12).
    03 Z309-CASH-SEQUENCE
                                  PICTURE 9(15).
  02 Z309-CATALOGER-NAME
                                  PICTURE X(10).
  02 Z309-CATALOGER-IP
                                  PICTURE X(20).
  02 Z309-DATE-X.
    03 Z309-DATE
                                  PICTURE 9(8).
    03 Z309-HOUR
                                  PICTURE 9(4).
  02 Z309-ACTION
                                  PICTURE 9(2).
  02 Z309-OVERRIDE
                                  PICTURE X(1).
  02 Z309-TEXT
                                  PICTURE X(50).
  02 Z309-DATA
                                  PICTURE X(2000).
```

Z309-REC-KEY			
Z309-ID	M	X(12)	DESC: ID of the patron of which the
			transaction is logged
			CONV: Valid patron ID
Z309-SEQUENCE	M	9(15)	DESC: Sequence number, unique and
			chronological. Used for sorting list in
			display.
			CONV: Must be unique. ALEPH's
			convention is time stamp + a running sequence (YYYYMMDD+ running
			sequence (11111WWDD+1ullilling sequence).
			For example: 200501130000001.
			The sequence is based on the
			last_record_sequence Oracle sequence
			that must be present in the pw_library.
Z309-REC-KEY-2			
Z309-LOAN-NUMBER	M/	9(9)	DESC: Contains the Z36-LOAN-
	О		NUMBER of the loan that is related to
			the log transaction. If the logged
			transaction is a cash transaction this field
			will be zeroes. CONV : Relevant loan number for all
			loan related actions or zeroes.
Z309-REC-KEY-3			loan related actions of zeroes.
Z309-DOC-NUMBER	M/	9(9)	DESC: Contains the Z30-DOC-
250) BOO HOMBER	O		NUMBER of the item related to the loan
			or cash transaction.
			CONV : Relevant value for all item
			related actions, or zeroes.
Z309-ITEM-SEQUENCE	M/	9(6)	DESC: Contains the Z30-ITEM-
	О		SEQUENCE of the item related to the
			loan or cash transaction.
			CONV : Relevant value for all item
7200 DEC VEV 4			related actions or zeroes.
Z309-REC-KEY-4 Z309-CASH-ID	N.17	V(12)	DESC: Contains the Z31-ID of the cash
Z309-CASH-ID	M/ O	X(12)	transaction that is logged in this
			transaction.
			CONV: Relevant Z31-ID for all cash
			related actions or zeroes.
Z309-CASH-SEQUENCE	M/	9(15)	Contains the Z31-SEQUENCE of the
	О		cash transaction that is logged in this
			transaction.
			CONV : Relevant Z31- SEQUENCE for

			all cash related actions or zeroes.
Z309-CATALOGER-NAME	M	X(10)	DESC: This field contains the user name of the librarian who performed the logged transaction. CONV: Use 'CONV' as a default or operator's user name.
Z309-CATALOGER-IP	M	X(20)	DESC: This field contains the workstation's identifier (if defined) or the internal IP of the workstation from which the transaction was performed. CONV: Relevant IP or blank
Z309-DATE-X			
Z309-DATE	M	9(8)	DESC: Contains the date that the logged transaction occurred. CONV: Relevant date or zeroes.
Z309-HOUR	M	9(4)	DESC: Contains the hour that the logged transaction occurred. CONV: Relevant hour or zeroes.
Z309-ACTION	M	9(2)	transaction which originates from the table tab_circ_log.lng. CONV: Following is the list of action codes and their meaning. 00 - Log loan note 01 - Regular loan 09 - Self check loan 02 - Offline circulation loan 03 - Regular return 06 - Late return 07 - Late recall return 08 - Late return within grace period 10 - Self check return 25 - Loan returned and placed in transit 04 - Offline circulation return 05 - Loan deleted 11 - Staff renewal 12 - Web renewal 13 - Batch renewal 14 - Self Check renewal 15 - Courtesy letter created 16 - Overdue letter created 17 - Loan declared lost 18 - Loan claimed returned 19 - Online recall 20 - Batch recall 21 - Recall cancelled 22 - Due date changed backward

	T	1	, -
			23 - Due date changed forward
			24 - Return date changed
			26 - Self check cancel renewal
			27 - Self check cancel loan
			28 - Loan to sponsor
			29 - Not On Loan Return
			30 - In House Use
			50 - Log cash note
			51 - Cash transaction created
			52 - Cash transaction fully paid
			53 - Cash transaction partially paid
			54 - Cash transaction fully waived
			55 - Cash transaction partially waived
			56 - Cash transaction exported
			57 - Cash transaction imported
			58 - Cash transaction updated to paid
			(batch)
			59 - Notice to patron of money owed
			60 - Self check cancel return
Z309-OVERRIDE	M		DESC: A Y/N flag that indicates
250) 0 (21442)	1,1		whether the logged action was performed
			when login override was in effect.
			CONV: Y for all actions that were
			performed while login override was in
			effect. N for all actions that were
			performed when login override was not
			in effect
Z309-TEXT	О	X(50)	DESC: Description of the action defined
			in the library's table tab_circ_log.lng.
			(e.g. "Regular loan")
			CONV: Relevant string or blanks
Z309-DATA	О	X(2000)	DESC: Expanded description of the
		[[[[]	logged transaction defined in the
			circ_logger file of the alephe/error_lng
			directory.
			CONV: Relevant string or blanks.
	<u> </u>		COLVE Relevant string of blanks.