

Z602 – SUBLIBRARY / ORDERING UNIT (for BUDGETS, VENDORS, and USERS)

The Z602 contains the sublibraries or the ordering units assigned to records. It is relevant to the vendor record (Z70), the budget record (Z76), and the user's password record (Z66). If the vendor, the budget, or the user is not linked to a specific sublibrary or ordering unit, the Z602 is not generated.

If the ordering unit mechanism is not used (the USE-ORDER-UNIT flag in the data_tab/tab100 table is set to 'N'), the Z602 record contains sublibrary codes. If the ordering unit mechanism is used, then this record contains ordering units.

Note that for sites that work with a two-level vendor setup (the TWO-LEVEL-VENDOR flag in the data_tab/tab100 table is set to 'Y'), regarding vendor usage permissions, there is no need for matching Z602 records for the sublibrary or ordering unit of the vendor specific records. The vendor's generic record will automatically be granted usage permissions for the sublibrary or ordering unit defined in the vendor specific records.

In the following table, (X) denotes an alphanumeric field and (9) denotes a numeric field. All alphanumeric fields are left-aligned with trailing spaces; all numeric fields are right-aligned with leading zeroes. Decimal positions are indicated by the symbol V. The total number of decimal digits is designated by the number of nines following the V.

```
02 Z602-REC-KEY.
   03 Z602-KEY-TYPE          PICTURE X(5) .
   03 Z602-KEY-TEXT         PICTURE X(50) .

02 Z602-SUB-LIBRARY-X.
   03 Z602-SUB-LIBRARY     OCCURS 500 PICTURE X(5) .
```

Z602-REC-KEY			
Z602-KEY-TYPE	M	X(5)	DESC: Name of the table to which the sublibrary or ordering unit is linked. The Z602-KEY-TYPE for vendors is Z70 , for budgets is Z76 , and for users is Z66 . CONV: Relevant table name.
Z602-KEY-TEXT	M	X(50)	DESC: Unique code by which the system identifies the vendor, the budget or the user. You may enter up to 50 alphanumeric characters. CONV: Relevant code according to Z70-VENDOR-CODE, Z76-BUDGET-NUMBER or Z66-USER-NAME.
Z602-SUB-LIBRARY-X			
Z602-SUB-LIBRARY OCCURS 100	M	X(5) OCCURS 500	DESC: Sublibrary code or ordering unit assigned to the vendor, the budget or the user. You may enter up to 500 codes. If the ordering unit mechanism is not used (the USE-ORDER-UNIT flag in the data_tab/tab100 table is set to 'N'), this field contains the relevant sublibrary code(s). If the ordering unit mechanism is used, then this field contains the relevant ordering unit(s). CONV: If the USE-ORDER-UNIT flag in the data_tab/tab100 table is set to 'N', enter valid sublibrary code(s) as define in the tab_sub_library table. If the flag is set to 'Y', enter valid ordering unit(s) as defined in the tab_sub_library table (sublibrary type 5).