## **Z123 – HISTORY (OPAC)**

The Z123 table contains the list of sets from previous OPAC searches saved by the user. Search sets saved in the History table are kept for future reference while records stored in the Previous Searches are deleted at the end of the session.

The Z123 table must be included in the file\_list of the library defined for the usr\_library variable of the aleph\_start file.

Conversion is not applicable.

In the following table, (X) denotes an alphanumeric field and (9) denotes a numeric field. All alphanumeric fields are left-aligned with trailing spaces; all numeric fields are right-aligned with leading zeroes. Decimal positions are indicated by the symbol V. The total number of decimal digits is designated by the number of nines following the V.

(	)2 Z123-REC-KEY.		
	03 Z123-ID	PICTURE	X(12).
	03 Z123-SEQUENCE	PICTURE	9(5).
(	)2 Z123-BASE	PICTURE	X(20).
(	)2 Z123-LIBRARY	PICTURE	X(5).
(	)2 Z123-ALPHA	PICTURE	X(1).
(	)2 Z123-REQUEST	PICTURE	X(500).
(	)2 Z123-LNG	PICTURE	X(30).
(	)2 Z123-DATE	PICTURE	9(8).
(	)2 Z123-NO-HITS	PICTURE	9(9).
(	)2 Z123-ADJACENCY	PICTURE	X(1).

Z123-REC-KEY			
Z123-ID	M	X(12)	<b>DESC:</b> User's identification key.
			Matches the Z303-ID field.
Z123-SEQUENCE	M	9(5)	<b>DESC:</b> Sequence number of the history
			record. Used to distinguish between
			history records.
Z123-BASE	M	X(20)	<b>DESC:</b> Base code of the base in which
			the search query was performed. Bases
			are defined in the tab_base table of the
			alephe_root tab directory.
Z123-LIBRARY	M	X(5)	<b>DESC:</b> Library code of the library in
			which the search request was performed.
Z123-ALPHA	M	X(1)	<b>DESC:</b> ALPHA code of the record. Use
			<b>L</b> for all scripts (e.g. Latin, Greek,
			Cyrillic, etc.).
Z123-REQUEST	M	X(500)	<b>DESC:</b> It contains the search query
			performed. For example: WRD =
			(polygon). It is copied from the Z05-
			REQUEST field of the set record.
Z123-LNG	M	X(30)	<b>DESC:</b> Borrower's selected interface
			language. This field is currently filled
			automatically by the system with the
			default value set in the root directory
			under www_server.conf (www_con_lng
			variable)
Z123-DATE	M	9(8)	<b>DESC:</b> Date the search request was
		Format:	performed and saved.
	3.5	YYYYMMDD	DDGG FILL GLILL
Z123-NO-HITS	M	9(9)	<b>DESC:</b> This field contains the number of
	3.5	77(4)	hits associated to the search query.
Z123-ADJACENCY	M	X(1)	<b>DESC:</b> Indicates whether or not the
			words in the find query are adjacent in
			the records. Values are 'Y' and 'N'. If the
			field is set to 'Y', this indicates that the
			user requested the words to be adjacent
			when performing the find query.