## **Z502** – Message for External Gateway (Oracle Queue)

A library may employ a third party gateway system that controls patron access to library services. Aleph is capable of making information available to be used by the gateway system. This information is stored in the Oracle Advanced Queue, which resides in the Aleph database (Z502).

Aleph merely makes the information available; the gateway system is responsible for accessing the information from the Aleph queue, analyzing it according to its own criteria, and determining whether to allow or block access to a patron.

In the following table, (X) denotes an alphanumeric field and (9) denotes a numeric field. All alphanumeric fields are left-aligned with trailing spaces; all numeric fields are right-aligned with leading zeroes. Decimal positions are indicated by the symbol V. The total number of decimal digits is designated by the number of nines following the V.

```
01
    Z502.
      02 Z502-EVENT-TIME
                               PICTURE X(15).
      02 Z502-EVENT-LIBRARY
                               PICTURE X(5).
      02 Z502-EVENT-TYPE
                               PICTURE X(2).
      02 Z502-USER-ID
                               PICTURE X(12).
      02 Z502-EVENT-ID
                               PICTURE X(50).
      02 Z502-EVENT-FIELD-1
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-2
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-3
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-4
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-5
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-6
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-7
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-8
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-9
                               PICTURE X(100).
      02 Z502-EVENT-FIELD-10
                               PICTURE X(100).
```

Z502-EVENT-TIME	M	X(15)	<b>DESC:</b> Time stamp, when the transaction
			took place. YYYYMMDDHHMMSSS
Z502-EVENT-	M	X(5)	<b>DESC:</b> The library where the event occurred
LIBRARY			
Z502-EVENT-TYPE	M	X(2)	<b>DESC:</b> the type of the event:
			PC – photocopy created
			PS – photocopy supplied
			PR – photocopy refused
			PD – photocopy deleted
			LC – loan created
			LD – loan deleted
			LR – loan returned



			7
			UC – user ID created UD – user ID deleted UB – user barcode updated
			MC – local patron record created ED – expiry date changed SC – patron status changed
			BC – block created BU – block updated BD – block deleted
Z502-USER-ID	M	X(12)	<b>DESC:</b> Patron's internal ID.
Z502-EVENT-ID		X(50)	<b>DESC:</b> relevant ID according to event type: photocopy related events: Z38-NUMBER
	'		Loan related events: Z30-BARCODE
	'		User id related events: Z308-KEY-DATA
	'		Local patron record related events: Z305-
	'		SUB-LIBRARY
	<u> </u>		Block related events: Z303-DELINQ-N
Z502-EVENT-FIELD-1	О	X(100)	<b>DESC:</b> additional information of the event.
thru	'		The data of this field depends on the event
EVENT-FIELD-10	'		type.