

Implementation Instructions for SFX December 2018 Service Pack

1. Add the option to select several categories and sub-categories in the Journal Search

For the following file:

templates/journalsearch/categories_list.tpl

Add the yellow rows:

```
<TMPL_LOOP NAME='category_loop'>
  <ul tabindex="0" data-attr="<TMPL_VAR ESCAPE=HTML NAME='category_id'>" class="subcategory-list mdl-list
<TMPL_UNLESS 'category_selected'>hidden</TMPL_UNLESS">
  <TMPL_LOOP NAME='subcategory_loop'>
    <li tabindex="0" <TMPL_IF RTL_DIR><TMPL_VAR LABEL_AUTO_DIR></TMPL_IF> class="mdl-list__item <TMPL_VAR
NAME='subcategory_selected'>" data-val="<TMPL_VAR ESCAPE=HTML NAME='subcategory_id'>"
onclick="selectListItemCategory(event)">
```

For the following file:

templates/js/journalsearch/journalSearch.js

In the 'selectListItem' function:

Replace the row:

```
if(event.ctrlKey && $(event.target).parents('.subcategory-list').length){
```

With:

```
if((event.metaKey || event.ctrlKey) && $(event.target).parents('.subcategory-list').length){
```

2. Adjusted behavior of the link display to the SFX menu. In case no parser or parse param exist for a target service, the target service is not linkable (same behavior as in SFX menu).

For the following file:

templates/journalsearch/results_full_view.tpl

Add the yellow rows:

```
<div class="layout-column full_flex_wrap">
  <TMPL_IF IS_LINKABLE>
    <div>
      <a onclick="show_report_broken_link_hyperlink('srv_num<TMPL_VAR ESCAPE=HTML NAME=OP_ID>')"
href="<TMPL_INCLUDE openurl_filtered.tpl">" target="<TMPL_VAR NAME='LINK_TARGET_ATTRIBUTE'>" class="sfx-
source-link sfx-external-source text-bold">
      <span dir="auto"><TMPL_VAR NAME='SERVICE_NAME'> <TMPL_VAR NAME='TARGET_NAME'></span>
      <i class="sfx-external-icon material-icons">open_in_new</i>
    </a>
    <TMPL_IF name="ADD_REPORT_BROKEN_LINK">
      <span class="report_broken_link_hyperlink">
        <span id="link_for_report_broken_link_az_srv_num<TMPL_VAR ESCAPE=HTML NAME=OP_ID>"
class="Exl_hide"></span>
        <a tabindex="0" id="srv_num<TMPL_VAR ESCAPE=HTML NAME=OP_ID>-reportlink" class="Exl_hide
Exl_broken_link <TMPL_IF IS_RTL>Exl_text_right</TMPL_IF"> title="<TMPL_VAR NAME='MESSAGE ("SFX Menu
Main","BrokenLinks--Link wording")' ESCAPE=HTML">" onclick="reportBrokenLinkFromResults(this, '<TMPL_VAR
ESCAPE=HTML NAME=OBJECT_ID>', '<TMPL_VAR ESCAPE=HTML NAME=OP_ID>')">
        <TMPL_VAR NAME='MESSAGE("SFX Menu Main","BrokenLinks--Link wording")' ESCAPE=HTML>
      </a>
      <span class="report_broken_link_thank_you report_broken_link_thank_you_short_srv_num<TMPL_VAR
NAME=OP_ID> Exl_hide"><TMPL_VAR NAME='MESSAGE("SFX Menu Main","BrokenLinks--thank you short")'
ESCAPE=HTML></span>
    </span>
  </TMPL_IF>
</div>
<TMPL_ELSE>
  <a class="sfx-source-link sfx-external-source text-bold">
```

```

    <span dir="auto"><TMPL_VAR NAME='SERVICE_NAME'> <TMPL_VAR NAME='TARGET_NAME'></span>
  </a>
</TMPL_IF>

```

```
<TMPL_IF 'AvailabilityInformation_SHOW'>
```

3. Fixed the problem with atitle field not being displayed in SFX Menu when OpenURL genre=patent

In case of localizations to the files described below, please following the instructions to ensure you will benefit from the fix in this ServicePack:

- templates/simplified_template1/banner.tpl
- templates/simplified_template1/mobile/banner.tpl
- templates/direct_link/banner.tpl
- templates/direct_link/mobile/banner.tpl
- templates/sfxmenu/banner_js.tpl
- templates/simplified_template1/banner_js.tpl
- templates/sfxmenu/banner.tpl

For the following file:

templates/simplified_template1/banner.tpl

Add the yellow rows:

```

<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
    <TR>
      <th <TMPL_VAR PADED>><TMPL_VAR ESCAPE=HTML NAME='MESSAGE("SFX Menu Main", "Headline--
Title")'>:</th>
      <TD <TMPL_VAR TXT_STYLE>><TMPL_VAR NAME="ATITLE" ESCAPE='HTML'></TD>
    </TR>
  </TMPL_IF>
</TR>

```

For the following file:

templates/simplified_template1/mobile/banner.tpl

Add the yellow rows:

```

<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
    <h1>
      <strong>
        <TMPL_VAR ESCAPE=HTML NAME='MESSAGE("SFX Menu Main", "Headline--Title")'>:
      </strong>
      <TMPL_IF TITLE_LTR><span class="bidi"> </TMPL_IF>
      <TMPL_VAR NAME="ATITLE" ESCAPE='HTML'>
      <TMPL_IF TITLE_LTR></span></TMPL_IF>
    </h1>
  </TMPL_IF>
</h2>
  <strong><TMPL_VAR ESCAPE=HTML NAME='MESSAGE("SFX Menu Main", "Headline--Source")'>:</strong>

```

For the following file:

templates/direct_link/banner.tpl

Change the rows in red:

```

< <TMPL_IF BANNER_TYPE_3>
  <TMPL_IF TITLE>
    <div class="Exl_title_banner">
      <h2 id="title_banner" title="<TMPL_VAR NAME="TITLE" ESCAPE='HTML'>"><TMPL_VAR
NAME="TITLE" ESCAPE='HTML'></h2>
    </div>
  </TMPL_IF>
  <span>
    <TMPL_IF NUMBER>
      [<TMPL_VAR NAME="NUMBER" ESCAPE='HTML'>]

```

To:

```

<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
    <div class="Exl_title_banner">
      <h2 id="title_banner" title="<TMPL_VAR NAME="ATITLE" ESCAPE='HTML'>"><TMPL_VAR
NAME="ATITLE" ESCAPE='HTML'></h2>
    </div>
  <TMPL_ELSE>
    <TMPL_IF TITLE>
      <div class="Exl_title_banner">
        <h2 id="title_banner" title="<TMPL_VAR NAME="TITLE"
ESCAPE='HTML'>"><TMPL_VAR NAME="TITLE" ESCAPE='HTML'></h2>
      </div>
    </TMPL_IF>
  </TMPL_IF>
  <span id="subtitle_banner"
  <TMPL_IF ATITLE>
    <TMPL_IF TITLE>
      title="<TMPL_VAR NAME="TITLE" ESCAPE='HTML'>"><TMPL_VAR NAME="TITLE"
ESCAPE='HTML'>
    </TMPL_IF>
  </TMPL_IF>
</span>
  <span>
    <TMPL_IF NUMBER>
      [<TMPL_VAR NAME="NUMBER" ESCAPE='HTML'>]

```

For the following file:

[templates/direct_link/mobile/banner.tmpl](#)

Change the rows in red:

```

<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF TITLE>
    <h1 title="<TMPL_VAR NAME="TITLE" ESCAPE='HTML'>"><TMPL_VAR NAME="TITLE" ESCAPE='HTML'></h1>
  </TMPL_IF>
  <h2>
    <TMPL_IF NUMBER>
      [<TMPL_VAR NAME="NUMBER" ESCAPE='HTML'>]

```

To:

```

<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
    <h1 title="<TMPL_VAR NAME="ATITLE" ESCAPE='HTML'>"><TMPL_VAR NAME="ATITLE"
ESCAPE='HTML'></h1>
  <TMPL_ELSE>
    <TMPL_IF TITLE>
      <h1 title="<TMPL_VAR NAME="TITLE" ESCAPE='HTML'>"><TMPL_VAR NAME="TITLE"
ESCAPE='HTML'></h1>
    </TMPL_IF>
  </TMPL_IF>
  <h2>
    <TMPL_IF ATITLE>
      <TMPL_IF TITLE>
        <TMPL_VAR NAME="TITLE" ESCAPE='HTML'>
      </TMPL_IF>
    </TMPL_IF>
  <TMPL_IF NUMBER>
    [<TMPL_VAR NAME="NUMBER" ESCAPE='HTML'>]

```

For the following file:

templates/sfxmenu/banner_js.tpl

Add the yellow rows:

```
<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>

tm.write('<b> Title:</b>');
tm.write(' <TMPL_VAR NAME="ATITLE" ESCAPE='HTML'>');
tm.write('<BR>');
  </TMPL_IF>

tm.write('          <B>Source:</B>');
tm.write(' <h1 lang="<TMPL_VAR NAME="OBJECT_LANG_CODE" ESCAPE='HTML'>"> ');
```

For the following file:

templates/simplified_template1/banner_js.tpl

Add the yellow rows:

```
<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
tm.write('<b> <TMPL_VAR ESCAPE=HTML NAME='MESSAGE("SFX Menu Main","Headline--Title")'>:</b>');
tm.write(' <TMPL_VAR NAME="ATITLE" ESCAPE='HTML'>');
tm.write('<BR>');
  </TMPL_IF>

tm.write('          <B><TMPL_VAR ESCAPE=HTML NAME='MESSAGE("SFX Menu Main","Headline--Source")'>:</B>');
  <TMPL_IF TITLE>
tm.write('          <TMPL_VAR NAME="TITLE" ESCAPE='HTML'>');
```

For the following file:

templates/sfxmenu/banner.tpl

Add the yellow rows:

```
<TMPL_IF BANNER_TYPE_3>
  <TMPL_IF ATITLE>
    <TR valign="top">
      <TD class="LabelBold">Title:</TD>
      <TD class="Label"><TMPL_VAR NAME="ATITLE" ESCAPE='HTML'></TD>
    </TR>
  </TMPL_IF>
  <TR valign="top">
    <TD class="LabelBold">Source:</TD>
    <TD class="Label">
      <h2 class="exlHeadingTextDisplay" lang="<TMPL_VAR NAME="OBJECT_LANG_CODE"
ESCAPE='HTML'>">
```

4. Fixed the problem with title search in book section of Fetch Item

For the following file:

templates/js/fetchitem/fetchItem.js

Add the red commands, and remove the green command:

```
var genre = $('input[name="rft.genre"]:checked').val();
var bookChapter = $("#book_chapter").val();
// Book chapter value should be sent to SFX as atitle value Jira-7039
```

```

if (genre == "book" || genre == "bookitem") {
    // Book shouldn't get 'title_search' type
    $("#title_search").val("");

    // Book chapter value should be sent to SFX as atitle value Jira-7039
    if (bookChapter) {
        $('input[name="rft.genre"]:checked').val('bookitem');
        $('input[name="rft.atitle"]').val(bookChapter);
    }
    else {
        $('input[name="rft.genre"]:checked').val('book');
        $('input[name="rft.atitle"]').val('');
    }
}
$("#is_submit").val("1");

```

5. Fixed the Apache error message when searching for category without sub-category in Journal Search

For the following file:

[templates/js/journalsearch/journalSearch.js](#)

Add the yellow rows in the 'validationProcess' function:

```

// Authors Validation
var aulast = $("#param_aulast_value").val();
var aufirst = $("#param_aufirst_value").val();
if(!aulast && aufirst){
    $("#param_aulast_value").parent().addClass('is-invalid');
    isValid = false;
}

// selected category must have at lease on selected sub-category
var selectedCat = $("#param_category_value").val();
var selectedSubCat = $("#param_subcategory_value").val();
if(selectedCat && selectedCat.length > 0 && selectedSubCat.length <= 0){
    isValid = false;
    alert($("#alertNoSubCatMessage").val());
}

return isValid;

```

For the following file:

[templates/journalsearch/categories_list.tmpl](#)

Add the yellow rows:

```




<label for="categories">
    <i aria-label="<TMPL_VAR NAME='MESSAGE("AZ_journalSearch","Vocal--SelectFromCategoryDropdown")'
ESCAPE=HTML">" class="mdl-icon-toggle__label material-icons <TMPL_IF
RTL_DIR>rtl_keyboard_arrow_down</TMPL_IF">keyboard_arrow_down</i>
</label>

```

6. Fixed the problem with 'Search by vendor' not working

For the following file:

[templates/js/journalsearch/journalSearch.js](#)

Add the yellow text:

```

function validationProcess() {
    isValid = true;

    // Authors Validation
    var aulast = $("#param_aulast_value").val();
    var aufirst = $("#param_aufirst_value").val();
    if(!aulast && aufirst){
        $("#param_aulast_value").parent().addClass('is-invalid');
        isValid = false;
    }

    // selected category must have at lease on selected sub-category
    var selectedCat = $("#param_category_value").val();
    var selectedSubCat = $("#param_subcategory_value").val();
    if(selectedCat && selectedCat.length > 0 && selectedSubCat.length <= 0){
        isValid = false;
        alert($("#alertNoSubCatMessage").val());
    }

    return isValid;
}

```